

# s.QUAD ATEX

Digital and analog

SWISSPHONE



## Alerting in hazardous areas

The sturdy, convenient pager was designed for individuals who work in dangerous environments and have to be reachable at all times. The pager can even be used in the most sensitive zones without risk thanks to its protective measures and because it is passive to radiation. The s.QUAD ATEX fulfils the requirements of the chemical and petrochemical industries.

### Key performance features

- )) Intrinsically safe, ideal choice for alerting in hazardous areas  
(Approved according to (Ex) II 2G Ex ib IIC T4)
- )) Usable in highly flammable gas-air mixtures
- )) Outstanding reception performance with 2.5  $\mu\text{V}/\text{m}$  at 1200 bit/s
- )) Programmable receiving frequency within switching bandwidth. Wide PLL up to 10 MHz (VHF), 20 MHz (UHF)
- )) 64 select as well as toggle profiles available
- )) Alerting volume > 95 dB(A) at 30 cm distance
- )) Multi-coloured alarm LED
- )) Five-level display of signal strength (RSSI)
- )) High-resolution display for over 200 characters per page
- )) Extremely robust (2-m drop test), dust and waterproof
- )) Optional: Analog pager, IDEA™ message encryption (128 bit), Multi-channel and scanner



# S.QUAD ATEX

	Performance features	Technical data	
<b>Standards, compliance, environmental conditions</b>	Standards	ETSI EN 300 390 ETSI EN 300 296 EN 60068-2-27 EN 60068-2-6 EN 60068-2-32 EN 60529	(digital) (analog) (shock) (vibration) (2-m drop test) (IP67)
	Compliance	(Ex) II 2G Ex ib IIC T4	
	Temperature range	-20 °C to +55 °C (rechargeable) -20 °C to +50 °C (with alkaline dry cell)	
<b>Main characteristics</b>	Frequency bands (additional frequencies on request)	VHF 4 m band VHF 2 m band UHF 70 cm band	81-88 MHz 138-146/146-155/155-164/164-174 MHz 430-450/450-470 MHz
	Frequency processing	PLL, frequency can be adjusted in the entire frequency band with programming software	
	Channel spacing	12.5, 20/25 kHz	
	Sensitivity* * typical value at 2 m band (best position on «salty man»)	at 512 bit/s at 1200 bit/s at 2400 bit/s	2.0 µV/m 2.5 µV/m 3.0 µV/m
	Signal strength display (RSSI)	5-level display	
	Addresses	<ul style="list-style-type: none"> <li>• 64 primary addresses (RICs) with four sub-addresses each, frame-independent</li> <li>• 64 addresses (ZVEI1, CCIR1 / free)</li> <li>• 256 address names with eight characters</li> </ul>	
	Alerting	<ul style="list-style-type: none"> <li>• Volume &gt; 95 dB(A) at 30 cm distance</li> <li>• Audio alarm tones</li> <li>• Vibration alarm</li> <li>• Multi-coloured Alarm-LED, seven colours can be individually programmed</li> <li>• Up to 64 user profiles or selectable addresses</li> </ul>	
	Messages	<ul style="list-style-type: none"> <li>• Over 100 individual messages with up to 512 characters</li> <li>• 256 fixed texts with 32 storable characters each</li> <li>• Up to two additional messages folders</li> <li>• PIN protected message storage</li> </ul>	
	Supported	<ul style="list-style-type: none"> <li>• Express-Alarm®</li> <li>• On-Air programming</li> </ul>	
Options	<ul style="list-style-type: none"> <li>• IDEA™ encryption: (128 bit)</li> <li>• Multi-channel, scanner</li> </ul>		
<b>Display und housing</b>	Display	<ul style="list-style-type: none"> <li>• Greyscale display with high resolution (146 x 128 Pixel, 106 DPI)</li> <li>• White backlight</li> <li>• Displays more than 200 characters per page</li> <li>• Different font sizes with 6, 7 or 8 lines</li> <li>• Vertical and horizontal menu and font guidance (programmable)</li> <li>• Scrollable font</li> </ul>	
	Dimensions (H x W x D)	81 x 64 x 22 mm	
	Weight (including battery)	102 g / 108 g (NiMH battery/dry cell)	
<b>Connection possibilities</b>	Radio	RFID chip (Protocol: EPCglobal Class1 Gen2)	
<b>Power management</b>	Type of battery	NiMH plus battery (AAA) or alkaline dry cell (AA)	
	Operating times (eco mode)	<ul style="list-style-type: none"> <li>• Alkaline dry cell (1.5 V):</li> <li>• NiMH plus battery (1.2 V/1000 mAh):</li> </ul>	2200 h 1000 h
<b>Accessories</b>	Programming set	Programming cradle with Windows-based programming software	
	Chargers	<ul style="list-style-type: none"> <li>• Charger with relay and antenna connector</li> <li>• Multi charger</li> </ul>	
	Carrier bags	Clip holster (included), Leather case, Safety chain	